BEST AVAILABLE COPY

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 5 February 2004 (05.02.2004)

PCT

(10) International Publication Number WO 2004/011776 A3

(51) International Patent Classification⁷: 19/16, 43/10

E21B 7/20,

Lance [US/US]; 934 Caswell Court, Katy, TX 77450

(21) International Application Number:

PC17US2003/020870

2 July 2003 (02.07.2003)

(25) Filing Language:

English

(26) Publication Language:

(22) International Filing Date:

English

(30) Priority Data: 60/399,240

29 July 2002 (29.07.2002) US

(71) Applicant (for all designated States except US): ENVENTURE GLOBAL TECHNOLOGY [US/US]; 16200 A. Park Row, Houston, TX 77084 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): COOK, Robert,


(74) Agents: MATTINGLY, Todd et al.; Haynes and Boone, LLP, Suite 3100, 901 Main Street, Dallas, TX 75202 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO.

[Continued on next page]

(54) Title: METHOD OF FORMING A MONO DIAMETER WELLBORE CASING



(57) Abstruct: A method of forming a wellbore casing that includes positioning a first wellbore casing (14) within and coupling to a borehole (10), positioning a second wellbore casing (16) within the borehole that overlaps with and is coupled to the first wellbore casing (14), positioning a tubular liner (18) within the borehole that overlaps with and is coupled to at a least a portion of the second wellbore casing (16), extending the length of the borehole (10), decoupling the liner (18) from the second casing (16) and removing the liner from the borehole, and positioning a third wellbore casing (20) within the borehole that overlaps with and is coupled to the second wellbore casing (16).

WO 2004/011776 A3



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report
- with amended claims

(88) Date of publication of the international search report: 14 October 2004

Date of publication of the amended claims: 25 November 2004

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

AMENDED CLAIMS

[received by the International Bureau on 20 July 2004 (20.07.04); claims 21 to 30 added]

21. A method of forming a wellbore easing within a borehole that traverses a subterranean formation, comprising:

positioning a tubular liner within the borehole; extending the length of the borehole; removing the tubular liner from the borehole; positioning a wellbore casing within the borehole; and coupling the wellbore casing to the borehole.

22. A method of forming a wellbore casing within a borehole that traverses a subterranean formation, comprising:

positioning a first wellbore casing within and coupling the first wellbore casing to the borehole;

positioning a tubular liner within the borehole that overlaps with and is coupled to at least a portion of the first wellbore casing;

extending the length of the borehole;

decoupling the tubular liner from the first wellbore casing and removing the tubular liner from the borehole; and

positioning a second wellbore casing within the boychole that overlaps with and is coupled to the first wellbore casing.

23. A system for forming a wellbore casing within a berehole that traverses a subterranean formation, comprising:

means for positioning a tubular liner within the borehole;
means for extending the length of the borehole;
means for removing the tubular liner from the borehole;
means for positioning a wellbore casing within the borehole; and
means for coupling the wellbore casing to the borehole.

24. A system for forming a wellbore casing within a borehole that traverses a subterranean formation, comprising:

means for positioning a first wellbore easing within and coupling the first wellbore easing to the borehole;

means for positioning a tubular liner within the bircholc that overlaps with and is coupled to at least a portion of the first wellbore casing;

means for extending the length of the horehole;

means for decoupling the tubular liner from the first wellbore easing and removing the tubular liner from the borehole; and

means for positioning a second wellbore casing within the borehole that overlaps with and is coupled to the first wellbore casing.

25. A method of forming a wellbore casing within a borehole that traverses a subterranean formation, comprising:

positioning a first wellbore casing within and coupling the first wellbore casing to the borehole;

positioning a second wellbore casing within the borehole that overlaps with and is coupled to the first wellbore casing;

preventing the second wellbore casing from collapsing;

extending the length of the borehole; and

positioning a third wellbore casing within the borehole that overlaps with and is coupled to the second wellbore casing.

26. A method of forming a wellbore casing within a borehole that traverses a subterranean formation, comprising:

preventing the borehole from collapsing; extending the length of the borehole; positioning a wellbore casing within the borehole; and coupling the wellbore easing to the borehole.

27. A method of forming a wellbore easing within a borehole that traverses a subterranean formation, comprising:

positioning a first wellbore casing within and coupling the first wellbore casing to the borehole;

preventing the first wellbore casing from collapsing;

extending the length of the borehole; and

positioning a second wellbore casing within the borehole that overlaps with and is coupled to the first wellbore casing.

28. A system for forming a wellbore easing within a borehole that traverses a subterranean formation, comprising:

means for positioning a first wellbore easing within and coupling the first wellbore easing to the borehole;

means for positioning a second wellbore casing within the borehole that overlaps with and is coupled to the first wellbore easing;

means for preventing the second wellbore casing from collapsing;

means for extending the length of the borehole; and

means for positioning a third wellbore easing within the borchole that overlaps with and is coupled to the second wellbore easing.

29. A system for forming a wellbore easing within a borehole that traverses a subterranean formation, comprising:

means for preventing the borehole from collapsing;

means for extending the length of the borehole;

means for positioning a wellbore casing within the borehole; and

means for coupling the wellbore casing to the borehole.

30. A system for forming a wellbore casing within a borehole that traverses a subterranean formation, comprising:

means for positioning a first wellbore easing within and coupling the first wellbore easing to the borehole;

means for preventing the first wellbore casing from collapsing;

means for extending the length of the borehole; and

means for positioning a second wellbore casing within the borehole that overlaps with and is coupled to the first wellbore casing.

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 5 February 2004 (05.02.2004)

PCT

(10) International Publication Number WO 2004/011776 A3

(51) International Patent Classification⁷: 19/16, 43/10

E21B 7/20,

(21) International Application Number:

PCT/US2003/020870

(22) International Filing Date:

2 July 2003 (02.07.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/399,240

29 July 2002 (29.07.2002) US


- (71) Applicant (for all designated States except US): ENVENTURE GLOBAL TECHNOLOGY {US/US}; 16200 A. Park Row, Houston, TX 77084 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): COOK, Robert,

Lance [US/US]; 934 Caswell Court, Katy, TX 77450 (118)

- (74) Agents: MATTINGLY, Todd et al.: Haynes and Boone, LLP, Suite 3100, 901 Main Street, Dallas, TX 75202 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: METHOD OF FORMING A MONO DIAMETER WELLBORE CASING



(57) Abstract: A method of forming a wellbore casing that includes positioning a first wellbore casing (14) within and coupling to a borehole (10), positioning a second wellbore casing (16) within the borehole that overlaps with and is coupled to the first wellbore casing (14), positioning a tubular liner (18) within the borehole that overlaps with and is coupled to at a least a portion of the second wellbore casing (16), extending the length of the borehole (10), decoupling the liner (18) from the second casing (16) and removing the liner from the borehole, and positioning a third wellbore casing (20) within the borehole that overlaps with and is coupled to the second wellbore casing (16).

WO 2004/011776 A3

GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, Cl, CM, (88) Date of publication of the international search report: 14 October 2004

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US03/20870

A. CLAS	SIFICATION OF SUBJECT MATTER			
IPC(7)	: E21B 7/20, 19/16, 43/10		RECEIVE	
US CL	: 175/171; 166/380, 207, 208 International Patent Classification (IPC) or to both no	arional classification and IPC		
	DS SEARCHED		OCT 2 2 2004	
Minimum doo U.S. : 17	cumentation searched (classification system followed 75/171; 166/380, 207, 208, 206, 216, 217, 277	by classification symbols)	HAYNES & BOONE L	
Documentation	on searched other than minimum documentation to the	extent that such documents are included	in the fields searched	
Electronic da EAST: wellb	ata base consulted during the international search (nan ore, casing, coupling, liner, decoupling, expanding, n	ne of data base and, where practicable, s mono diameter	earch terms used)	
C. DOC	UMENTS CONSIDERED TO BE RELEVANT			
Category *	Citation of document, with indication, where ap	propriate, of the relevant passages	Relevant to claim No.	
Α	US 1,880,218 A (SIMMONS) 1 October 1930 (01.10.1930), Figures 3 and 4. US 6,543,552 B1 (METCALFE et al) 8 April 2003 (08.04.2003), Figures 1-5.		1, 3, 4, 6, 7, 11, 13, 14, 16, 17, 19, 20 1, 2, 11, 12	
A			1, 11	
Α	US 4,483,399 A (COLGATE) 20 November 1984 (20.11.1984), Figure 2.		1, 11	
A	US 6,598,678 B1 (SIMPSON et al) 29 July 2003 (29.07.2003), Figures 13 and 14.		1, 2, 11, 12	
Α	US 6,550,539 B2 (MAGUIRE et al) 22 April 2003 (22.04.2003), Figures 4a-4f.		1, 2, 11, 12	
Α	US 6,070,671 A (CUMMING et al) 6 June 2000 (06.06.2000), Figures 1-4.		3, 4, 6, 7, 9, 10, 13, 14, 16, 17, 19, 20	
Purthe	r documents are listed in the continuation of Box C.	See patent family annex.		
Special categories of cited documents: "A" document defining the general state of the art which is not considered to be		T° later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention		
of particular relevance "E" earlier application or patent published on or after the international filing date		considered novel or cannot be consid	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone	
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of mother citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means		ey" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art		
document published prior to the international filing date but later than the priority date claimed		್ಲಿ document member of the same patent family		
Date of the actual completion of the international search		Date of mailing of the international se	arch report	
17 October 2003 (17.10.2003)		Authorized officer 10		
	nailing address of the ISA/US	()3/11/F (MC		
Mail Stop PCT, Attn: ISA/US Commissioner for Patents		David Bagnah	ļ	
P.	O. Box 1450	Telephone No. 703-306-4198		
	lexandria, Virginia 22313-1450 No. (703)305-3230			
	A MIO (second shoot) (buly 1008)			

Form PCT/ISA/210 (second sheet) (July 1998)

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
□ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
□ FADED TEXT OR DRAWING
□ BLURRED OR ILLEGIBLE TEXT OR DRAWING
□ SKEWED/SLANTED IMAGES
□ COLOR OR BLACK AND WHITE PHOTOGRAPHS
□ GRAY SCALE DOCUMENTS
□ LINES OR MARKS ON ORIGINAL DOCUMENT
□ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

□ OTHER: _____

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.